Customer :

Attention:

Your ref. No:

Your Part. No: 29 0024

No. KX-97-1799

Date: Feb. 19. 1997

SPECIFICATIONS

ALPS' ;

MODEL 29 0024

Spec. No. :

Sample No. : W1011765M

RECEIPT STATUS

RECEIVED

By. Date

Signature

Name

Title

ALPS ELECTRIC CO., LTD.

HEAD OFFICE
1-7, YUKIGAYA-OHTSUKA-CHO,
OHTA-KU, TOKYO 145 JAPAN

DSG'D H. Kimura

APP'D Y. Ohya

ENG. DEPT. DIVISION

Sales

No. KX-97-1799

SPECIFICATIONS

1. THIS SPECIFICATIONS APPLY TO RK09K1130 · POTENTIOMETERS.

2. CONTENTS OF THIS SPECIFICATIONS.

W1011765M
K091C0Z4G

3. MARKING

·MARKING ON ALL UNITS
DATE CODE, RESIST. VALUE, TAPER

4. REMARKS

· NOTES

·METHOD OF MARKING
TO BE STAMPED WITH BLACK INK OR LASER MARKING
·This unit uses polycarbonate. To be careful for using this unit in such violent gas atmospheric condition as ammonia, amine, alkaline aqueous solution, aromatic hydrocarbon, keton, ester, alkyl hydrocarbon, etc.

SPECIFICATIONS

ELECTRICAL

1. Total resistance : 100kΩ ±20%
2. Rated power : 0.05 W
3. Rated voltage :
   The rated voltage shall be the voltage of D.C. or A.C. (commercial frequency, effective value) corresponding to the rated power (dissipation), and be obtained from the following formula. When the obtained rated voltage exceeds the maximum working voltage given in the following, however, the maximum working voltage of the following shall be the rated voltage.

   $E = \sqrt{P \cdot R}$ (V)

   Where E : Rated voltage (V)
   P : Rated power (dissipation) (W)
   R : Nominal total resistance (Ω)

   Maximum working voltage : 50 V A.C. , 20 V D.C.

4. Residual resistance between terminals
   between term. 1&2. term. 2&3 : 300Ω max.
5. Sliding noise : Less than 100 mV measured by method of JIS C 6443.
6. Insulation resistance : Greater than 100 MΩ measured by D.C. 250V.
7. Withstand voltage: More than 1 minute with an application of A.C. 250 V.
8. Taper : B

MECHANICAL

1. Overall rotational angle : 280°±5°
2. Operation torque : 10~80 gf·cm
3. Shaft end stop strength : 3 Kgf·cm MIN.
4. Starting toruque : 100 gf·cm MAX.
5. Resistance to soldering heat :
   After soldering (Less than 300°C and quicker than 3 seconds) there shall be no evidence of poor contact between resistance element and terminals, or any physical damages as a result of the test.
6. Play of shaft :
   The resistor shall be mounted by soldering the mounting legs on the panel, and a side thrust of 250 gf·cm at the end of the shaft shall be applied, then the total play of the shaft shall not exceed 0.5 × L / 20 mm p-p.
7. Eccentricity of shaft :
   The eccentricity of the root of shaft shall not exceed 0.35mm against the center of the mounting position.
8. Robustness of shaft against end thrust :
   The shaft shall withstand against end thrust of not less than 5 Kgf for 3 seconds.
9. Robustness of shaft against side thrust :
   The shaft shall withstand against side thrust of not less than 4 Kgf·cm for 3 seconds on the end of the shaft at right angles to the axis of the shaft after mounting the resistor by soldering.

ENDURANCE

1. Rotational life : 5,000 cycles min.

NOTE


1. The items except above mentioned items shall meet or exceed JIS C 6443.
2. Operating temperature :-10°C~+60°C. 3. Storage temperature :-30°C~+70°C.

ALPS ELECTRIC CO., LTD.

SYMB	DATE	APPD	CHKD	DSGD	APPD.	CHKD.	DSGD.	TITLE
					Sep. 13. '96	Sep. 13. '96	Sep. 13. '96	
					S. Aizawa	M. Satoh	Y. Saitoh	DOCUMENT NO. W1011765M

KY


ALPS ELECTRIC CO., LTD
1-7 YUKIGAYA OTSUKA-CHO OTA-KU TOKYO JAPAN



AT 140° C.W. SHAFT ROTATION FROM FULL C.C.W. POSITION VOLTAGE PERCENT SHALL FALL WITHIN THE LIMITS OF 40~60 PERCENT.

SYMB	DATE	APPD	CHKD	DSGD	APPD.	CHKD.	DSGD.	NAME
					Jul. 13. '93	Jul. 13. '93	Jul. 13 '93	RESISTANCE TAPER (B)
					K. Nagami	K. Sasaki	K. Suzuki	DOCUMENT NO. W1011765M

KX09



製品重量：1.8 g
NET WEIGHT

指定なき部分の許容差 TOLERANCES UNLESS OTHERWISE SPEC	
L≦10	±0.3
10＜L＜100	±0.5
100≦L	±0.8
角度 ANGULAR DIMENSION	±5°

PART NO.	NAME	MATERIAL NAME / CODE	FINISH
—	—	—	SHAFT COLOR : BLACK (B)

ALPS ELECTRIC CO., LTD.

SYMB	DATE	APPD	CHKD	DSGD

DSGD. 設計者 Y. Saitoh 96-09-13	SCALE 2 : 1	W1011765M	
CHKD. Y. Satoh 96-09-13		TITLE 9形1軸単連絶縁軸VR	
APPD. S. Aizawa 96-09-13	UNIT mm	DOCUMENT NO. K091C0Z4G	F18